



AXIS Q60 Series

	AXIS Q6075 	AXIS Q6075-E 
Max. video resolution	1920x1080 (2.1 MP)	1920x1080 (2.1 MP)
Sensor size/Lens/ Horizontal field of view	1/2.8" 4.25–170 mm, F1.6–4.95, 62.8° – 2.23°	1/2.8" 4.25–170 mm, F1.6–4.95, 65.1°–2.0°
Day and night	✓	✓
Min. illumination (lux) Color/B&W	0.1/ 0.002	0.1/ 0.002
Max. frames per second	50/60	50/60
Optical zoom	40	40
Audio support/ Built-in mic	✓ / -	- / -
Product specific analytics (for standard analytics, see page 43)	AXIS Guard suite Active gatekeeper Autotracking 2 Standard analytics	AXIS Guard suite Active gatekeeper Autotracking 2 Standard analytics
Power	High PoE Midspan included	High PoE SFP midspan included
In-/output ports	4	-
Operating temperature	0 °C to 50 °C (32 °F to 122 °F)	-50 °C to 50 °C (-58 °F to 122 °F)
Outdoor ready approvals	-	IP66/IP67/NEMA 4X
WDR	WDR	WDR
Lightfinder	Lightfinder 2.0	Lightfinder 2.0
Zipstream/H.264/H.265	✓ / ✓ / ✓	✓ / ✓ / ✓
OptimizedIR/Built-in IR	- / -	- / -
Special features	Electronic image stabilization Secure boot FIPS 140-2 certified TPM 2.0 module Orientation aid Automatic defog, Focus recall, IK10 Enter/Exit detector Object counter Object removed Shock detection Highlight compensation	Electronic image stabilization Secure boot FIPS 140-2 certified TPM 2.0 module Orientation aid Automatic defog Focus recall, IK10 Enter/Exit detector Object counter Object removed Shock detection Highlight compensation